

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE


In re Patent Application of

SYMES

Serial No. 09/960,728

Filed: September 24, 2001

For: SINGLE INSTRUCTION MULTIPLE DATA PROCESSING



Atty. Ref.: 550-258

Group:

Examiner:

* * * * *

December 13, 2001

Assistant Commissioner for Patents
Washington, DC 20231

SUBMISSION OF PRIORITY DOCUMENTS

Sir:

It is respectfully requested that this application be given the benefit of the foreign filing date under the provisions of 35 U.S.C. §119 of the following, a certified copy of which is submitted herewith:

Application No.

0024312.1

Country of Origin

United Kingdom

Filed

4 October 2000

Respectfully submitted,

NIXON & VANDERHYE P.C.

By: _____

A handwritten signature in black ink, appearing to read "Stanley C. Spooner", written over a horizontal line.

Stanley C. Spooner

Reg. No. 27,393

SCS:kmm

1100 North Glebe Road, 8th Floor

Arlington, VA 22201-4714

Telephone: (703) 816-4000

Facsimile: (703) 816-4100

THIS PAGE BLANK (USPTO)



INVESTOR IN PEOPLE


The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



Signed

Dated


29 August 2001

THIS PAGE BLANK (USPTO)



Request for a grant of a patent

(See the notes on the back of this form you can also get an explanatory leaflet from the Patent Office to help you fill in this form)



1. Your reference P009835GB

2. Patent application number
(The Patent Office will assign a number)

0024312.1

- 4 OCT 2000

3. Address and postcode of the applicant
(underline all surnames)

ARM Limited
110 Fulbourn Road
Cherry Hinton
Cambridge
CB1 9NJ
United Kingdom

Patents ADP number (if you know it)

7498124002

If the applicant is a corporate body, give the country/state of its incorporation

United Kingdom

05OCT00 E573476-21 002246
F01/7700 0.00-0024312.1

4. Title of the invention SINGLE INSTRUCTION MULTIPLE DATA PROCESSING

5. Name of your agent (if you have one) D YOUNG & CO

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

21 NEW FETTER LANE
LONDON
EC4A 1DA

Patents ADP number (if you know it)

59006 ✓

6. If you are declaring priority from one or more earlier patent applications, give the country and date of filing of the or each of these earlier applications and (if you know it) the or each application number

1st

2nd

3rd

Country

Priority application number
(if you know it)

Date of filing
(day/month/year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and filing date of the earlier application


Number of earlier application

Date of filing
(day/month/year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Y' s' if:

a) any applicant named in part 3 is not an inventor, or
b) there is an inventor who is not named as an applicant, or
c) any named applicant is a corporate body.
See note (d))

Yes

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document	Continuation sheets of this form	0
	Description	7
	Claim(s)	3
	Abstract	1
	Drawing(s)	4
10. If you are also filing any of the following, state how many against each item	Priority Documents	0
	Translation of Priority Documents	0
	Statement of inventorship and right to grant of a patent (Patents Form 7/77)	2
	Request for preliminary examination and search (Patents Form 9/77)	1
	Request for substantive examination (Patents Form 10/77)	0
	Any other documents (Please specify)	0
11.	I/We request the grant of a Patent on the basis of this application.	
	Signature 	Date
	D YOUNG & CO	4 Oct 2000
	Agents for the Applicants	
12. Name and daytime telephone number of person to contact in the United Kingdom	Nigel Robinson	023 80634816

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

a) If you need help to fill in this form or you have any questions, please contact the Patent Office on 01645 500505.


b) Write your answers in capital letters using black ink or you may type them.

c) If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheets should be attached to this form.

d) If you answered 'Yes' Patents Form 7/77 will need to be filed.

e) Once you have filled in the form you must remember to sign and date it.

f) For details of the fee and ways to pay please contact the Patent Office.



**Statement of inventorship and
of right to grant of a patent**



The Patent Office
Cardiff Road
Newport
Gwent NP9 1RH

1. Your reference P009835GB

2. Patent application number (if you know it) - 4 OCT 2000

3. **0024312.1** ARM Limited

4. Title of the invention SINGLE INSTRUCTION MULTIPLE DATA
PROCESSING

5. State how the applicant(s) derived the right from the inventor(s) to be granted a patent By Virtue of Employment

6. How many, if any, additional Patents Forms 7/77 are attached to this form? (see note (c)) 0

7. I/We believe that the person(s) named over the page
(and on any extra copies of this forms) is/are the
inventor(s) of the invention which the above patent
relates to.

Signature Date

DY Robinson

D YOUNG & CO 4 Oct 2000
Agents for the Applicants

8. Name and daytime telephone number of person to contact in the United Kingdom 023 80634816 Nigel Robinson

Notes

a) If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.

b) Write answers in capital letters using black ink or you may type them.

c) If there are more than three inventor, please write the names and addresses of the other inventors on the back of another Patents Form 7/77 and attach it to this form.

d) When an application does not declare any priority, or declares priority from an earlier UK application, you must provide enough copies of this form so that the Patent Office can send one to each inventor who is not an applicant.

e) Once you have filled in the form you must remember to sign and date it.

THIS PAGE BLANK (USPTO)

D Young & Co ref: P009835GB

Enter the full names, addresses and postcodes of the inventors in the boxes and underline the surnames

Surname	<u>SYMES</u>
First Names	Dominic Hugo
Address	3 Applewood Close Cherry Hinton Cambridge CB1 9NU United Kingdom
7994601001	
Patents ADP number (if you know it):	

Surname	
First Names	
Address	
Patents ADP number (if you know it):	

Surname	
First Names	
Address	
Patents ADP number (if you know it):	

Reminder:
Have you signed the form?

THIS PAGE BLANK (USPTO)

SINGLE INSTRUCTION MULTIPLE DATA PROCESSING

This instruction relates to the field of data processing systems. More particularly, this invention relates to a data processing system in which it is desired to provide single instruction multiple data type operation.

5 Single instruction multiple data operation is a known technique whereby data words being manipulated in accordance with a single instruction in fact represent multiple data values within those data words with the manipulation specified being independently performed upon respective data values. This type of instruction can increase the efficiency with which a data processing system may operate and is
10 particularly useful in reducing code size and speeding up processing operation.. The technique is commonly, but not exclusively, applied to the field of manipulating data values representing physical signals, such as in digital signal processing applications.

When extending the data processing capabilities of a data processing system, an important consideration is the extent of any size, complexity, cost and power
15 consumption overheads that may be introduced to support the additional processing capability. Measures that can add processing capability whilst reducing the additional overhead incurred are strongly advantageous.

Viewed from one aspect the present invention provides apparatus for processing data, said apparatus comprising: a shifting circuit; and a bit portion
20 selecting and combining circuit; and an instruction decoder responsive to an instruction to control said shift circuit and said bit portion selecting and combining circuit to perform an operation upon a data word R_n and a data word R_m , wherein said operation yields a value given by: selecting a first portion of bit length A of said data word R_n extending from one end of said data word R_n ; selecting a second portion of
25 bit length B of said data word R_m starting from a bit position specified as a shift operand within said instruction; and combining said first portion and said second portion to form respective different bit position portions of an output data word R_d .

The invention provides an efficient packing instruction that allows different portions of two input operand data words to be combined within a packed output data
30 word using a single instruction. Furthermore, the invention provides a shift operand that allows one of the data words being packed to be selected from a variable position

within its input operand data word in a manner that provides the ability to combine an additional data manipulation with the packing operation, e.g. one of the portions to be combined into the packed output data word may be multiplied or divided by a power of two at the same time that it is being packed together with another data word portion.

- 5 This contrasts with a system which may only pack together data words from fixed positions within input operand data words. The invention recognises that a packing operation is a relatively simple operation for the data path of a data processing system to perform and accordingly additional functionality may be added to the packing operation utilising circuit elements already present within the data path and without
10 introducing processing cycle time constraints.

It will be appreciated that the fixed position multibit portion taken from one end of an input operand data word could be taken from either the most significant bit end or the least significant bit end of that input operand data word. These possibilities correspond to the packing of the top halves of words or the bottom halves of words in
15 common terminology.

Particularly preferred embodiments of the invention are ones in which the first portion and the second portion abut within the output data word and the first portion and the second portion are of equal length and together fill the output data word.

- In many real life DSP situations it is convenient that the data word halves have
20 a bit length of sixteen.

The additional functionality of the instruction of the present invention may be particularly conveniently provided in systems within which a shifting circuit is provided upstream of a selecting and combining circuit within the data path. The selecting and combining circuit may conveniently be disposed in parallel with an
25 arithmetic circuit within the data path as it is not desired to combine the packing operation with a function provided by the arithmetic circuit.

Viewed from another aspect the present provides a method of data processing, said method comprising the steps of decoding and executing an instruction that yields a value given by: selecting a first portion of bit length A of said data word R_n
30 extending from one end of said data word R_n; selecting a second portion of bit length B of said data word R_m starting from a bit position specified as a shift operand within

said instruction; and combining said first portion and said second portion to form respective different bit position portions of an output data word Rd.

The invention also provides a computer program product storing a computer program for controlling a general purpose computer to act in accordance with the
5 above techniques. In particular, the invention provides a computer program including an instruction for controlling a computer to perform the operation as set out above.

Embodiments of the invention will now be described, by way of example only, with reference to the accompanying drawings in which:

Figure 1 schematically illustrates the action of a first SIMD type data
10 processing instruction;

Figure 2 schematically illustrates a data path within a processing apparatus of a type well suited to executing the data processing instruction of Figure 1;

Figures 3 and 4 schematically illustrate two variants of a further SIMD type data processing instruction; and

15 Figure 5 schematically illustrates data path of a data processing system well suited for executing the data processing instructions of Figures 3 and 4.

Figure 1 illustrates the action of a first SIMD type data processing instruction termed ADD8TO16. This instruction comes in both signed and unsigned variants corresponding to the nature of the extension added to the front of a selected portion of
20 each of the input operand data words as it is extended in length as part of the processing performed. The first input operand data word is stored within a register Rm of the data processing apparatus. The data word is formed of four 8-bit portions p0, p1, p2 and p3. Depending upon whether or not a rotate right operation of 8-bit positions is specified in the instruction, either the multibit portions p0 and p2 or
25 alternatively the multibit portions p1 and p3 are selected out of the input data word within register Rm. The example illustrated in Figure 1 shows the non-adjacent portions p0 and p2 being selected in the unrotated (shifted) variant with the other variant being indicated by the dotted lines.

When the multibit portions have been selected, each is promoted in length from
30 8 bits to 16 bits using either zero or sign extension. The shaded portions of the promoted data word P shown in Figure indicate these extension portions.

The second input data word is stored within a register R_n and comprises two 16-bit data values. The example illustrated performs a single-instruction-multiple-data add operation whereby the extended p_0 value is added to the lower 16 bit value a_0 of R_n whilst the extended p_2 value is added to the upper 16 bit portion a_2 of the R_n value. This type of addition is one which may be considered as a full width addition with the carry chain broken between the 15th and 16th bits of the result. It will be appreciated that other SIMD type arithmetic operations may be performed, such as, for example, a SIMD subtraction.

The output result data word generated by the instruction of Figure 1 produces in the lower 16 bits the sum of p_0 and a_0 whilst the upper 16 bits contain the sum of p_2 and a_2 . This instruction is particularly useful in operations that determine the sum of absolute differences between respective data values whereby the a_0 and a_2 represent accumulate values with the values p_0 to p_3 representing individual absolute values of signal difference values, such as pixel difference values. This type of operation is commonly needed in MPEG motion estimation processing and the ability to perform this operation at high speed is strongly advantageous.

Figure 2 illustrates an example data path 2 of a data processing system that may be used to implement the instruction of Figure 1. A register bank 4 holds 32-bit data words to be manipulated. Both the input operand data words stored in R_m and R_n are read from this register bank and the result data word is written back to register R_d in the register bank 4. The data path 2 includes a shifting circuit 6 and an adder circuit 8. The many other data processing instructions provided by the system utilise this shifting circuit 6 and adder circuit 8 in various different ways. Such a data path 2 is carefully designed so that the time taken for a data value to propagate through the shifting circuit 6 and the adder circuit 8 is well matched to the data processing cycle time. Efficient use of the hardware resources of the data path 2 is made in systems in which those resources are active for a high proportion of every data word propagating through the data path 2. A sign/zero extending and masking circuit 10 is provided in parallel with lower portion of the shifting circuit 6. A multiplex 12 is able to select either the output of the full shifting circuit 6 or the output of the sign/zero extending and masking circuit 10 as one of the inputs to the adder circuit 8. The other input to the adder circuit 8 is the input operand data word of R_n .

When executing the instruction of Figure 1, the input operand data word of Rm is supplied to the shifting circuit 6 in which an optional right shift of 8-bit positions is applied to the data word in dependence upon whether or not that parameter was specified within the instruction. Within a multilevel multiplexer based shifter, such a restricted possibility shift may be provided relatively simply from a first portion of the shifting circuit 6 (e.g. in the case of a 32-bit system the first level of multiplexer may provide 16 bits of shift and the second level of multiplexer provides 8 bits of shift). Accordingly, a value optionally shifted by the specified amount can be tapped off from part way through the shifting circuit 6 and supplied to the sign/zero extending and masking circuit 10. This circuit 10 operates to mask out the non-selected multibit portions of the possibly shifted input operand data word of Rm and replace these masked out portions with either zeros or a sign extension of their respective selected multibit portions. The output of the sign/zero extending and masking circuit 10 passes via a multiplexer 12 to a first input of the adder circuit 8. The second input of the adder circuit 8 is the input operand data word of Rn. The adder circuit 8 performs a SIMD add upon its inputs (i.e. two parallel 16-bit adds with the carry chain effectively broken between bit positions 15 and 16). The output of the adder circuit 8 is written back into register Rd of the a register bank 4.

Figures 3 and 4 illustrate two variants of a half word packing SIMD type instruction. The PKHTB instruction of Figure 3 takes a fixed top half of one input operand data word stored in register Rn and a variable position half bit portion of a second input operand data word stored in register Rm and combines these into respectively the top half and the bottom half of an output data word to be stored in register Rd. The instruction PKHBT takes the bottom half of an input operand data word of Rn and a variable position half word length portion of a second input operand data word of Rm and combines these respectively into the bottom and top halves of an output data word of Rd. It will be seen that the selected portion of the input operand data word of Rn in either case is unshifted in its location within the output data word Rd. This allows this portion to be provided by a simple masking or selecting circuit representing very little additional hardware overhead. The variable position half word portion of the instruction of Figure 3 is selected from bit positions 15 to 0 of the word of Rm after that word has been right shifted by k bit positions. Similarly, the half

word length variable position portion of R_m selected in accordance with the instruction of Figure 4 is selected from bit positions 31 to 16 of the word of R_m after that word has been left shifted by k bit positions.

5 The variable shifting provided in combination with the packing function of the instructions of Figure 3 and Figure 4 is particularly useful for adjusting changes in the "Q" value of fixed point arithmetic values that can occur during manipulation of those values.

10 Figure 5 illustrates a data path 14 that is particularly well suited for performing the instructions of Figures 3 and 4. A register bank 16 again provides the input operand data words, being 32-bit data words in this example, and stores the output data word. The data path includes a shifting circuit 18, an adder circuit 20 and a selecting and combining circuit 22.

15 In operation, the unshifted input operand data word of R_n passes directly from the register bank 16 to the selecting and combining logic 22. In the case of instruction of Figure 3, the most significant 16 bits of the value of R_n are selected and form the corresponding bits within the output data word R_d . In the case of the instruction of Figure 4 it is the least significant 16 bits of the input operand data word of R_n that are selected and passed to form the least significant bits of the output data word R_d . The input operand data word of R_m passes through the full shifting circuit 18. In the case
20 of the instruction of Figure 3, an arithmetic right shift of k bit positions is applied and then the least significant 16 bits from the output of the shifting circuit 18 are selected by the selecting and combining circuit 22 to form the least significant 16 bits of the output data word of R_d . In the case of the instruction of Figure 4, the shifting circuit 18 provides a left logical shift of k bit positions and supplies the result to the selecting
25 and combining circuit 22. The selecting and combining circuit 22 selects the most significant 16 bits of the output of the shifting circuit 18 and uses these to form the most significant 16 bits of the output data word of R_d .

30 It will be seen that the selecting and combining circuit 22 is provided in a position in parallel with the adder circuit 20. Accordingly, given that the data path 14 is carefully designed to allow for a full shift and add operation to be performed within a processing cycle, the relatively straight forward operation of selecting and combining

can be provided within the time period normally allowed for the operation of the adder circuit 20 without imposing any processing cycle constraints.

5 It will be understood that the data processing instructions explained above and as defined in the claims have been defined in terms of the result value achieved. It will be appreciated that the same result value can be achieved with many different processing steps and orders of steps. The invention encompasses all of these variants that produce the same final result value using a single instruction.

CLAIMS

1. Apparatus for processing data, said apparatus comprising:
a shifting circuit; and
a bit portion selecting and combining circuit; and
5 an instruction decoder responsive to an instruction to control said shifting circuit and said bit portion selecting and combining circuit to perform an operation upon a data word R_n and a data word R_m , wherein said operation yields a value given by:
selecting a first portion of bit length A of said data word R_n extending from
10 one end of said data word R_n ;
selecting a second portion of bit length B of said data word R_m starting from a bit position specified as a shift operand within said instruction; and
combining said first portion and said second portion to form respective different bit position portions of an output data word R_d .
15
2. Apparatus as claimed in claim 1, wherein said first portion extends from a most significant bit end of said data word R_n .
3. Apparatus as claimed in claim 1, wherein said first portion extends from a least
20 significant bit end of said data word R_n .
4. Apparatus as claimed in any one of claims 1, 2 and 3, wherein said shift operand can specify any bit position within said data word R_m .
- 25 5. Apparatus as claimed in any one of the preceding claims, wherein said first portion and said second portion abut within said output data word R_d .
6. Apparatus as claimed in claim 5, wherein said output data word has a bit length of C and $C = A + B$.
30
7. Apparatus as claimed in claim 6, wherein $A = B$.

8. Apparatus as claimed in any one of the preceding claims, wherein $A = 16$.
9. Apparatus as claimed in any one of the preceding claims, wherein $B = 16$.
- 5 10. Apparatus as claimed in any one of the preceding claims, wherein said instruction is a single-instruction-multiple-data instruction.
11. Apparatus as claimed in any one of the preceding claims, wherein said
10 instruction combines a data value pack operation with a shift operation.
12. Apparatus as claimed in any one of the preceding claims, wherein said shifting circuit is upstream of said selecting and combining circuit in a data path of said apparatus.
- 15 13. Apparatus as claimed in claim 12, wherein said selecting and combining circuit is disposed in parallel to an arithmetic circuit within said data path.
14. A method of data processing, said method comprising the steps of decoding
20 and executing an instruction that yields a value given by:
selecting a first portion of bit length A of said data word R_n extending from one end of said data word R_n ;
selecting a second portion of bit length B of said data word R_m starting from a bit position specified as a shift operand within said instruction; and
25 combining said first portion and said second portion to form respective different bit position portions of an output data word R_d .
15. A computer program product comprising a computer program for controlling a computer to perform a method as claimed in claim 14.
- 30 16. Apparatus substantially as hereinbefore described with reference to the accompanying drawings.

17. A method substantially as hereinbefore described with reference to the accompanying drawings.
- 5 18. A computer program product substantially as hereinbefore described with reference to the accompanying drawings.

ABSTRACT**SINGLE INSTRUCTION MULTIPLE DATA PROCESSING**

5 A data processing system is provided with an instruction (PKH) that combines
a packing operation of respective portions of input operand data words (R_n , R_m) into
an output data word (R_d) together with the ability to select one of the portions to be
combined from a variable position (k) within its respective input operand data word in
a manner that allows additional processing to be carried out together with the packing
operation. The instruction conveniently combines either the top or bottom half of one
of the input operand data words with a half data word portion selected from a variable
10 position within the other input operand data word.

[Figure 3.]

THIS PAGE BLANK (USPTO)

1/4




Fig. 1

THIS PAGE BLANK (USPTO)






Fig. 2

THIS PAGE BLANK (USPTO)



PKH TB $R_d, R_n, R_m, ASL\#k$



PKH BT $R_d, R_n, R_m, LSL \#k$

THIS PAGE BLANK (USPTO)




Fig. 5

09/960,728

THIS PAGE BLANK (USPTO)